

Application No. 10/616,219

Attorney Docket No. 03P01822US01

IN THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) A system for providing a user interface presenting a plurality of patient medical parameter data parameters, comprising:
an acquisition processor for acquiring, from a patient monitoring device, data representing a plurality of patient parameter parameters; and
a processor for initiating generation of data representing ~~at least one~~ a single display image including,
 - (a) a plurality of current value values of a said plurality of patient parameter parameters and
 - (b) a sliding bar representation of each of said plurality of patient parameter current value values of said plurality of patient parameters together with a corresponding range indicator indicators for graphically indicating whether each of said current value values is ~~out side~~ outside of a corresponding user determined range wherein said range indicators correspond to a plurality of different value ranges individually having range limit identifiers with a common visual display attribute with a current value indicator image element when said current value is within an individual range and said current value indicator image element having a second visual display attribute different from said first visual display attribute when said current value is outside said individual range.
2. (Currently Amended) A system according to claim 1, wherein
~~said sliding bar representation includes a current value indicator image element and a range limit identifier image element having a common display attribute when said current value is within said range limit~~ said image element common display attribute comprises a particular image element color.

- 2 -

BEST AVAILABLE COPY

Application No. 10/616,219

Attorney Docket No. 03P01822US01

3. (Currently Amended) A system according to claim 1, wherein
said image element common display attribute comprises at least one of, (a) a
~~particular image element color~~ a particular image element fill pattern, (b) a particular
image element shape, (c) a particular image element type of highlighting, (d) a particular
image element foreground or background, (e) a particular type of image element shading,
and (f) a particular image element outline, ~~and (g) a particular image element fill pattern.~~

4. (Currently Amended) A system according to claim 1, wherein
said sliding bar representation user determined range includes at least ~~one~~ two of,
(a) a normal range indicator, (b) a cautionary range indicator and (c) an excessive range
indicator and graphically indicates where said current value is within a range.

5. (Original) A system according to claim 1, wherein
said sliding bar representation includes a current value indicator image element and
a plurality of range limit identifier image elements corresponding to a plurality of value
ranges and an individual range limit identifier has a common display attribute with said
current value indicator image element when said current value is within said individual
range.

6. (Original) A system according to claim 5, wherein
said plurality of ranges comprise at least two of, (i) a normal range, (ii) a cautionary
range and (iii) an excessive range and
said image element common display attribute comprises at least one of, (a) a
particular image element color, (b) a particular image element shape, (c) a particular image
element type of highlighting, (d) a particular image element foreground or background, (e)
a particular type of image element shading, (f) a particular image element outline, and (g) a
particular image element fill pattern.

Application No. 10/616,219

Attorney Docket No. 03P01822US01

7. (Currently Amended) A system according to claim 1, wherein
said ~~at least one~~ single display image includes at least one of, (a) a value of said patient parameter received prior to said current parameter value, (b) a normal value of said patient parameter, (c) a time interval substantially indicative of time between measurement of said current parameter value and a previously received parameter value, (d) a patient parameter label.

8. (Original) A system according to claim 7, wherein
a patient parameter label has a common display attribute with another different patient parameter label, said display attribute comprising at least one of, (a) a particular image element color, (b) a particular image element shape, (c) a particular image element type of highlighting, (d) a particular image element foreground or background, (e) a particular type of image element shading, (f) a particular image element outline, and (g) a particular image element fill pattern.

9. (Original) A user interface system according to claim 1, wherein
said patient parameter comprises at least one of, (a) a blood pressure parameter, (b) a ventilation parameter, (c) a vital sign parameter, (d) a blood oxygen concentration representative parameter, (e) a spontaneous tidal volume parameter, (f) a respiratory rate parameter, (g) a positive end-expiratory pressure parameter, (h) a temperature, (i) a heart rate, (j) a cardiac output, (k) an infusion pump parameter associated with fluid delivery, (l) a drip medication related parameter and (m) another fluid related parameter.

10. (Currently Amended) A system according to claim 1, wherein
said single display image includes a plurality of individual current values and associated sliding bar representations of individual patient parameters oriented in said single display image in a rotational orientation; and

said sliding bar representation represents at least one of, (a) a linear scale, (b) a logarithmic scale.

Application No. 10/616,219

Attorney Docket No. 03P01822US01

11. (Currently Amended) A system according to claim 10, wherein
said single display image includes a plurality of individual current values and individual current values and associated sliding bar representations of individual patient parameters are oriented in said single display image in at least one of, (a) a horizontal orientation and (b) a vertical orientation; and

said sliding bar representation includes a current value indicator image element and a range limit identifier image element positioned at user determined positions indicative of proportions of slide bar full scale,

12. (Original) A system according to claim 1, wherein
said sliding bar representation comprises at least one of, (a) a bar along a single axis, (b) a bar along an axis at an angle from horizontal, (c) a curved bar, (d) a rotary bar and (e) a bar along a plurality of axes.

13. (Currently Amended) A system for providing a user interface presenting a plurality of patient medical parameters, comprising:

an acquisition processor for acquiring, from a patient monitoring device, data representing a plurality of patient parameters; and

a processor for initiating generation of data representing a single display image including,

(a) a plurality of current values of a plurality of patient parameters and

(b) sliding bar representations of said plurality of current values of said plurality of patient parameters together with corresponding range indicators for graphically indicating whether said current values are ~~out-side~~ outside of corresponding user determined ranges and (i) said range indicators correspond to a plurality of different value ranges individually having range limit identifiers with a common display attribute with a current value indicator image element when said current value is within an individual range; and

Application No. 10/616,219

Attorney Docket No. 03P01822US01

wherein individual current values and associated sliding bar representations of individual patient parameters are ordered by type of associated patient parameter so that patient parameters that typically exhibit out of range conditions together are adjacent in said single display image.

14. (Currently Amended) A system according to claim 13, wherein said plurality of different value ranges comprise at least two of, (i) a normal range, (ii) a cautionary range and (iii) an excessive range and

individual current values and associated sliding bar representations of individual patient parameters are oriented in said single display image in ~~at least one of, (a) a rotational orientation, (b) a horizontal orientation and (c) a vertical orientation.~~

15. (Original) A system according to claim 13, wherein said plurality of patient parameters are selected from within groups of parameters including at least one of, (a) a vascular related group of parameters, (b) a respiratory related group of parameters and (c) a laboratory related group of parameters.

16. (Original) A system according to claim 15, wherein said processor receives patient mass and height information for use in computing body surface area and cardiac index.

17. (Cancelled)

18. (Currently Amended) A system for configuring a user interface display image for presenting patient medical parameter data, comprising:

a processor for initiating generation of data representing ~~at least one~~ a single display image including,

a linear sliding bar representation of a patient parameter value permitting user selection of a range limit identifier image element at a position indicative of a proportion

Application No. 10/616,219

Attorney Docket No. 03P01822US01

of slide bar full scale, said range limit identifier image element being for use in a patient parameter display image for graphically indicating whether a patient parameter current value is ~~outside~~ outside of a user determined range and said sliding bar representation of said patient parameter current value is presented together with corresponding range indicators for graphically indicating whether said patient parameter current value is outside of a plurality of corresponding different user determined ranges and said range indicators correspond to a plurality of value ranges individually having range limit identifiers with a common display attribute with a current value indicator image element when said current value is within an individual range.

19. (Currently Amended) A system according to claim 18, wherein
said ~~linear sliding bar representation permits user selection of a plurality of range limit identifier image elements corresponding to~~ plurality of corresponding different user determined ranges comprise at least two of, (a) a normal range indicator, (b) a cautionary range indicator and (c) an excessive range indicator and graphically indicates where said current value is within a range.

20. (Original) A system according to claim 18, wherein
said at least one display image includes data entry boxes enabling a user to enter at least one of, (a) a minimum parameter value, (b) a normal parameter value and (c) a maximum parameter value.

21. (New) The system according to claim 1, wherein
said plurality of current values of a plurality of patient parameters are displayed in a circular pattern representation enabling the user to more easily discern and detect changes and alarm situations.

Application No. 10/616,219

Attorney Docket No. 03P01822US01

22. (New) The system according to claim 13, wherein
said plurality of current values of a plurality of patient parameters are displayed in a
circular pattern representation enabling the user to more easily discern and detect changes
and alarm situations.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ **BLACK BORDERS**

☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☐ **FADED TEXT OR DRAWING**

☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☐ **GRAY SCALE DOCUMENTS**

☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.